

**HIKVISION®**



HUGE PANORAMAS.  
INCREDIBLE VIEW.  
**HIKVISION PanoVu SERIES**  
**NETWORK CAMERA**

**PanoVu**




## WHAT IS THE PANO VU CAMERA?

When designing surveillance applications, more and greater requirements have become necessary for monitoring large areas such as public plazas, arenas, airports, busy traffic intersections, and the like. In very large settings, security personnel need to see more with just one camera – not just a panoramic image, but zoomed-in, detailed views as well.

With that in mind, Hikvision designed the PanoVu Series all-in-one cameras to capture both excellent panorama and close-up details. Panoramic images are captured with multiple sensors, rendering 180° or 360° panoramic imaging with real-time ultra-HD resolution. The integrated design and high-speed pan-tilt-zoom action grants the user swift positioning over expansive areas with the power to bring sharp details into focus. At the same time, the PanoVu Series Cameras utilize Hikvision's ultra-low light Darkfighter technology, making colored images possible in poorly lit environments.

Now, new additions to the PanoVu product family feature high definition panoramic view camera – up to 32 MP – as well as supplemental IR & panoramic lighting for clear images in extremely dark environment, and an amazing wide tilt angle. And, because panoramic cameras demand more bandwidth and storage than conventional cameras, Hikvision designed the PanoVu cameras to utilize H.265+ technology, making the most efficient use of video transmission and storage.

PanoVu Mini Series cameras are new members to the Hikvision PanoVu product family. They feature compact sizes, affordable prices, and ease of installation and use, while keeping all the market-proven features of PanoVu cameras such as high edge definition, low image distortion, and powerful PTZ functions. They are used in a wide range of scenarios, indoor and outdoor.



## A SIMPLE SYSTEM FOR AN EASY INSTALLATION

With an "all-in-one" design, a single product serves as a system that enables front-end splicing and delivers both panorama and every detail through full shot (180° or 360°) and close-up shot without using any additional server. You can enjoy a simple and time-saving installation and maintenance. The product allows for a quick installation as dome camera does—all you need are a cable and a power supply. Characterized by a flexibility and ease of operation, it provides a full range of options in the user interface to offer a panorama in the ultra-high-resolution scene while capturing the details dynamically in real time. You can zoom in an image to its center to see the close-up details just by clicking on the image.



## PANORAMIC VIEWS AND FINER PICTURES

Combining several built-in horizontal cameras with PTZ power, one PanoVu camera captures 360° or 180° panoramic images as well as close-up images with up to 50x optical zoom. These cameras provide high-resolution images with more detail. Note, too, that the panoramic images are stitched together within the camera itself, so users will not need another server or add-on to enjoy full use of the cameras.



360° Overview + 50x PTZ



## DarkFighter ULTRA-LOW-LIGHT TECHNOLOGY AND SUPPLEMENTAL LIGHTING


All fixed and zoom lenses of PanoVu cameras utilize Hikvision DarkFighter ultra-low-light technology. Therefore, whether you are viewing 180° or 360° panoramic images or PTZ close-up images, each one can render colored images in very low-light environments down to 0.002 lux.

Supplemental lighting significantly improves image quality in extremely dark environment. But with a panoramic camera, it's difficult for supplemental light to reach the same angle as the lens. Hikvision's advanced PanoVu cameras, however, feature wide-angle supplemental light, perfectly matching the angle of the lens and bringing vivid images to life.



## SMART CODEC – H.265+ OPTIMIZED COMPRESSION


PanoVu Series Cameras also feature Hikvision's H.265+ technology, reducing bandwidth and storage requirements by an average of 70% or more while maintaining consistent resolution, framerates, and detail. It's an efficient way to manage super high resolution video footages.



24-Hour recording file size (GB) comparing H.264, H.265, and H.265+  
\*Data was tested in a common scene; for reference only.

## SMART FUNCTIONS

With advanced video analysis and multi-target tracking algorithms select, PanoVu Cameras also feature a wide range of smart functions in panoramic mode, including intrusion detection, line crossing detection, and region entrance and exiting detection. The PanoVus can also send alarm signals linked to the PTZ for tracking, greatly improving security efficiency.



# APPLICATION SCENARIOS

With intelligent and powerful features, the PanoVu Series Cameras can be used extensively, including applications like airports, transit stations, gymnasiums, scenic ports, and public squares needing a wide range of monitoring.



# PRODUCT FEATURES

## DS-2DP0818ZIX-D236

PanoVu Series 180° Panoramic + PTZ Camera



### Panoramic Camera

- Four 1/1.8" progressive scan CMOS
- Up to 4096 × 1800 resolution @ 30 fps
- Horizontal field of view: 180°, vertical field of view: 80°
- Min. illumination:
  - Color: 0.005 lux @ (F2.0, AGC ON)
  - B/W: 0.0005 lux @ (F2.0, AGC ON)

### Tracking PTZ Camera

- 1/1.8" progressive scan CMOS
- Up to 1920 × 1080 resolution @ 30 fps
- Pan and tilt range: 360° (Pan), -15° to 90° (Tilt)
- Min. illumination:
  - Color: 0.002 lux @ (F1.5, AGC ON)
  - B/W: 0.0002 lux @ (F1.5, AGC ON)
  - 0 lux with IR
- 36× optical zoom, 16× digital zoom
- IR distance: 200 m

## DS-2DP0818ZIX-D250

PanoVu Series 180° Panoramic + PTZ Camera



### Panoramic Camera

- Four 1/1.8" progressive scan CMOS
- Up to 4096 × 1800 resolution @ 30 fps
- Horizontal field of view: 180°, vertical field of view: 80°
- Min. illumination:
  - Color: 0.005 lux @ (F2.0, AGC ON)
  - B/W: 0.0005 lux @ (F2.0, AGC ON)

### Tracking PTZ Camera

- 1/2.8" progressive scan CMOS
- Up to 1920 × 1080 resolution @ 30 fps
- Pan and tilt range: 360° (Pan), -15° to 90° (Tilt)
- Min. illumination:
  - Color: 0.05 lux @ (F1.8, AGC ON)
  - B/W: 0.01 lux @ (F1.8, AGC ON)
  - 0 lux with IR
- 50× optical zoom, 16× digital zoom
- IR distance: 200 m
- Optical Image Stabilization

## DS-2DP0818ZIX-D836

PanoVu Series 180° Panoramic + PTZ Camera



### Panoramic Camera

- Four 1/1.8" progressive scan CMOS
- Up to 4096 × 1800 resolution @ 30 fps
- Horizontal field of view: 180°, vertical field of view: 80°
- Min. illumination:
  - Color: 0.005 lux @ (F2.0, AGC ON)
  - B/W: 0.0005 lux @ (F2.0, AGC ON)

### Tracking PTZ Camera

- 2/3" progressive scan CMOS
- Up to 4096 × 2160 resolution @ 30 fps
- Pan and tilt range: 360° (Pan), -15° to 90° (Tilt)
- Min. illumination:
  - Color: 0.005 lux @ (F1.5, AGC ON)
  - B/W: 0.0005 lux @ (F1.5, AGC ON)
  - 0 lux with IR
- 36× optical zoom, 16× digital zoom
- IR distance: 200 m

## PRODUCT FEATURES

### DS-2DP1636ZIX-D236

PanoVu Series 180° Panoramic + PTZ Camera



#### Panoramic Camera

- Eight 1/1.8" progressive scan CMOS
- Up to 2 × 4096 × 1800 resolution @ 30 fps
- Horizontal field of view: 360°, vertical field of view: 80°
- Min. illumination:
  - Color: 0.005 lux @ (F2.0, AGC ON)
  - B/W: 0.0005 lux @ (F2.0, AGC ON)

#### Tracking PTZ Camera

- 1/1.8" progressive scan CMOS
- Up to 1920×1080 resolution @ 30 fps
- Pan and tilt range: 360° (Pan), -15° to 90° (Tilt)
- Min. illumination:
  - Color: 0.002 lux @ (F1.5, AGC ON)
  - B/W: 0.0002 lux @ (F1.5, AGC ON)
  - 0 lux with IR
- 36× optical zoom, 16× digital zoom
- IR distance: 200 m

### DS-2DP1636ZIX-D250

PanoVu Series 360° Panoramic + PTZ Camera



#### Panoramic Camera

- Eight 1/1.8" progressive scan CMOS
- Up to 2 × 4096 × 1800 resolution @ 30 fps
- Horizontal field of view: 360°, vertical field of view: 80°
- Min. illumination:
  - Color: 0.005 lux @ (F2.0, AGC ON)
  - B/W: 0.0005 lux @ (F2.0, AGC ON)

#### Tracking PTZ Camera

- 1/1.8" progressive scan CMOS
- Up to 1920 × 1080 resolution @ 30 fps
- Pan and tilt range: 360° (Pan), -15° to 90° (Tilt)
- Min. illumination:
  - Color: 0.05 lux @ (F1.8, AGC ON)
  - B/W: 0.01 lux @ (F1.8, AGC ON)
  - 0 lux with IR
- 50× optical zoom, 16× digital zoom
- IR distance: 200 m
- Optical Image Stabilization

### DS-2DP1636ZIX-D836

PanoVu Series 360° Panoramic + PTZ Camera



#### Panoramic Camera

- Eight 1/1.8" progressive scan CMOS
- Up to 2 × 4096 × 1800 resolution @ 30 fps
- Horizontal field of view: 360°, vertical field of view: 80°
- Min. illumination:
  - Color: 0.005 lux @ (F2.0, AGC ON)
  - B/W: 0.0005 lux @ (F2.0, AGC ON)

#### Tracking PTZ Camera

- 2/3" progressive scan CMOS
- Up to 4096 × 2160 resolution @ 30 fps
- Pan and tilt range: 360° (Pan), -15° to 90° (Tilt)
- Min. illumination:
  - Color: 0.005 lux @ (F1.5, AGC ON)
  - B/W: 0.0005 lux @ (F1.5, AGC ON)
  - 0 lux with IR
- 36× optical zoom, 16× digital zoom
- IR distance: 200 m

### DS-2PT3122IZ-DE3

PanoVu Mini Series IR Network PTZ Camera



#### Panoramic Camera

- 1/2.8" progressive scan CMOS
- Up to 1920 × 1080 resolution @ 30 fps
- Min. illumination:
  - Color: 0.05 lux @ (F2.0, AGC ON)
  - B/W: 0.01 lux @ (F2.0, AGC ON)
  - 0 lux with IR
- Supports H.265 video compression
- Horizontal field of view: 128.5°

#### PTZ Camera

- 1/2.8" progressive scan CMOS
- Up to 1920 × 1080 resolution @ 30 fps
- Min. illumination:
  - Color: 0.05 lux @ (F2.0, AGC ON)
  - B/W: 0.01 lux @ (F2.0, AGC ON)
  - 0 lux with IR
- Supports H.265 video compression
- 4× optical zoom, 8× digital zoom

### DS-2PT3306IZ-DE3

PanoVu Mini Series IR Network PTZ Camera



#### Panoramic Camera

- Three 1/2.8" progressive scan CMOS
- Up to 3-ch 1920 × 1080 resolution @ 30 fps
- Min. illumination:
  - Color: 0.05 lux @ (F2.0, AGC ON)
  - B/W: 0.01 lux @ (F2.0, AGC ON)
  - 0 lux with IR
- Horizontal field of view: 128.5° × 3
- Vertical field of view: 75.7°
- Up to 10 m IR

### DS-2PT3326IZ-DE3

PanoVu Mini Series IR Network PTZ Camera



#### Panoramic Camera

- Three 1/2.8" progressive scan CMOS
- Up to 3-ch 1920 × 1080 resolution @ 30 fps
- Min. illumination:
  - Color: 0.05 lux @ (F2.0, AGC ON)
  - B/W: 0.01 lux @ (F2.0, AGC ON)
  - 0 lux with IR
- Supports H.265 video compression
- Horizontal field of view: 128.5° × 3

#### PTZ Camera

- 1/2.8" progressive scan CMOS
- Up to 1920 × 1080 resolution @ 30 fps
- Min. illumination:
  - Color: 0.05 lux @ (F2.0, AGC ON)
  - B/W: 0.01 lux @ (F2.0, AGC ON)
  - 0 lux with IR
- Supports H.265 video compression
- 4× optical zoom, 8× digital zoom

### DS-2PT5306BZ-DE

PanoVu Mini Series IR Network PTZ Camera



- Three 1/2.8" progressive scan CMOS
- Up to 3-ch 1920 × 1080 resolution @ 30 fps
- Min. illumination:
  - Color: 0.005 lux @ (F1.6, AGC ON)
  - B/W: 0.001 lux @ (F1.6, AGC ON)
  - 0 lux with IR
- Horizontal field of view: 80.7° × 3
- Vertical field of view: 43.5°
- Three flexible cameras are adjustable along a circular track with a sliding range of 0° to 270°
- Up to 30 m IR
- IP66

### DS-2PT5326IZ-DE

PanoVu Mini Series IR Network PTZ Camera



#### Panoramic Camera

- Three 1/2.8" progressive scan CMOS
- Up to 3-ch 1920 × 1080 resolution @ 30 fps
- Min. illumination:
  - Color: 0.005 lux @ (F1.6, AGC ON)
  - B/W: 0.001 lux @ (F1.6, AGC ON)
  - 0 lux with IR
- Horizontal field of view: 80.7° × 3
- Vertical field of view: 43.5°
- Up to 30 m IR

#### PTZ Camera

- 1/2.8" progressive scan CMOS
- Up to 1920 × 1080 resolution @ 30 fps
- Min. illumination:
  - Color: 0.005 lux @ (F1.6, AGC ON)
  - B/W: 0.001 lux @ (F1.6, AGC ON)
  - 0 lux with IR
- 10× optical zoom, 8× digital zoom
- Up to 50 m IR

### DS-2CD6D24/54FWD

8/20 MP PanoVu Vari-Focal Network Camera



- Four 1/2.7" progressive scan CMOS
- Up to 4-ch 2/5 MP resolution @ 30 fps
- Horizontal field of view: 31° to 108°
- Vertical field of view: 22.5° to 74.4°
- H.265, H.264
- Optical fiber transmission
- 10-30 m IR range
- Four flexible 2.8-12 mm VF lens
- 6 behavior analyses, 4 exception detection, and face detection

### DS-2CD6984G0

32 MP PanoVu Series Panoramic Dome Camera

NEW



- 1/2" progressive scan CMOS
- Max. resolution: 8160 × 3616 @ 25 fps in panorama display mode
- Panorama field of view:
  - 180° horizontal field of view
  - 95° vertical field of view
- Multiple display modes available
- Panorama, original, panorama + ePTZ, and divided panorama
- Four IR LEDs, up to 20 m IR
- H.265, H.265+, H.264+, H.264
- 120 dB WDR
- Image enhancement: BLC, 3D DNR, HLC, defog, EIS
- Audio and alarm I/O, optional
- Flexible power supply options
- IP67, IK10

### DS-2CD6924G0

8 MP PanoVu Series Panoramic Dome Camera



- 1/2.8" progressive scan CMOS
- 7008 × 1080 @ 30 fps in panorama mode
- Four 6 mm lenses
- Four IR LEDs, up to 20 m IR
- H.265, H.265+
- 3D DNR
- BLC/ROI/HLC
- Audio and alarm I/O (-S)
- 6 behavior analyses, audio exception detection and face detection

## Recommended NVRs

DS-9632/64NI-I8/I16 (I Series NVR)

DS-96064/128/256NI-I16/I24 (Super I Series NVR)

Embedded H.265 4K NVR



- 320/512/768 Mbps max. bit rate input (up to 32/64/128/256-ch IP video)
- Third-party network cameras supported
- Up to 12 MP resolution recording
- Supports H.265/H.265+/H.264/H.264+/MPEG4 video formats
- 2-ch HDMI and 2-ch VGA output interfaces provided, HDMI output at up to 4K (3840 × 2160) resolution
- Gigabit network interfaces
- 8/16 SATA, up to 2 eSATA, 2 USB 2.0 and 1 USB 3.0 interfaces
- Supports RAID 0, 1, 5, 6, 10



HUGE PANORAMAS.  
INCREDIBLE VIEW.  
**HIKVISION PANOVU SERIES**  
NETWORK CAMERA



Distributed by



**HIKVISION**<sup>®</sup>

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +6-032-7224000  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com

www.hikvision.com

Follow us on social media to get the latest product and solution information:

